

Platinum Resistance Temperature Detector


MH 1020

M series PRTDs are designed for large volume applications where long term stability, interchangeability and accuracy over a large temperature range are vital. Typical applications are Automotive, White goods, HVAC, Energy management, Medical and Industrial equipment.

Nominal Resistance R_0	Tolerance	Order No. Plastic bag
100 Ohm at 0°C	DIN EN 60751, class B	32 207 711
	DIN EN 60751, class A	32 207 572
500 Ohm at 0°C	DIN EN 60751, class B	32 207 712
1000 Ohm at 0°C	DIN EN 60751, class B	32 207 713
	DIN EN 60751, class A	32 207 573

The measuring point for the nominal resistance is defined at 8 mm from the end of the sensor body.

Specification	DIN EN 60751 (according to IEC 751)
Temperature range	-70°C to 600°C (continuous operation) Tolerance class B: - 70°C to + 600°C Tolerance class A: - 50°C to + 300°C
Temperature coefficient	TCR = 3850 ppm/K
Leads	AuPd
Long-term stability	max. R_0 -drift 0.04% after 1000 h at 600°C
Vibration resistance	at least 40 g acceleration at 10 to 2000 Hz, depends on installation
Shock resistance	at least 100 g acceleration with 8ms half sine wave, depends on installation
Environmental conditions	unhoused for dry environments only
Insulation resistance	> 100 M Ω at 20°C; > 2 M Ω at 500°C
Self heating	0.2 K/mW at 0°C
Response time	water current ($v = 0.4$ m/s): $t_{0.5} = 0.12$ s; $t_{0.9} = 0.30$ s air stream ($v = 2$ m/s): $t_{0.5} = 6.0$ s; $t_{0.9} = 20.0$ s
Measuring current	100 Ω : 0.3 to 1.0 Ma 500 Ω : 0.1 to 0.7 mA 1000 Ω : 0.1 to 0.3 mA (self heating has to be considered)



Note Other tolerances, values of resistance and wire lengths are available on request.

We reserve the right to make alterations and technical data printed. All technical data serves as a guideline and does not guarantee particular properties to any products.

Heraeus Sensor Technology GmbH, Reinhard-Heraeus-Ring 23, 63801 Kleinostheim, Germany
Phone: +49 (0) 6181/35-8098, Fax: +49 (0)6181/35-8101, E-Mail: info.HSND@Heraeus.com, Web:www.heraeus-sensor-technology.com