

# Vertical Stainless Steel

## Miniature Internal Side Mount SSF24

The SSF24 series is a compact horizontally mounted device designed to achieve reliable switching.

Mounting is in the side of the tank from the inside, so requires access to the inside of the tank.

They are manufactured in 316 grade Stainless Steel, and will work in liquids of SG 0.8 minimum.

The switch action may be reversed by removing the float, inverting it and then refitting it to the stem.

- Stainless steel
- Internal mounting
- Compact design
- Temperature range to 120°C
- User configurable N/O or N/C action

### Technical specifications

Mounting style	Internal	Cable length - standard	350
Mounting thread	1/8" BSP	Cable size	17/0.10 - AWG22
Float & Stem material	316 grade	Cable conductor material	Tinned copper
Maximum Temperature	120°C	Cable sheath material	XLPE
Maximum Pressure	10 bar	Cable temperature rating	125°C
Float SG	0.7	Sealing gasket	Not supplied
Minimum fluid SG	0.8	Tightening torque for fixing nut	2.0kg/cm

### Electrical specifications

Contact type	N/O or N/C
Switching Power VA Max.	50
Switching Current Max. A	0.5
Switching Voltage AC Max.	300
Switching Voltage DC Max.	300
Breakdown Voltage Min. DC	600

All ratings are for resistive load only

### Standard Parts

SSF24X035

### Leadouts

35cm XLPE wires



### Outline dimensions

