

High Pressure Side Mount SSF29

The SSF29 series is a horizontally mounted device designed to achieve reliable switching at higher pressures. Mounting is in the side of the tank from the inside, so requires access to the inside of the tank.

This type is capable of working at pressures of up to 40 bar.

They are manufactured in 316 grade Stainless Steel, for those liquids and environments that require the use of Stainless Steel and will work in liquids of SG 0.7 minimum.

The switch action may be reversed by removing the float, inverting it and then refitting it to the stem.

- Stainless steel
- Internal mounting
- Temperature range to 120°C
- Pressure up to 40 bar
- User configurable N/O or N/C action

Technical specifications

Mounting style	Internal	Cable length - standard	350
Mounting thread	1/8" BSP	Cable size	17/0.10 - AWG22
Float & Stem material	316 grade	Cable conductor material	Tinned copper
Maximum Temperature	120°C	Cable sheath material	XLPE
Maximum Pressure	40 bar	Cable temperature rating	125°C
Float SG	0.6	Sealing gasket	Not supplied
Minimum fluid SG	0.7	Tightening torque for fixing nut	2.0kg/cm

Electrical specifications

Contact type	N/O or N/C
Switching Power Max. VA	50
Switching Current Max. A	0.5
Switching Voltage Max. AC	300
Switching Voltage Max. DC	300
Breakdown Voltage Min. DC	600

All ratings are for resistive load only

Standard Parts

SSF29X035

Leadouts

35cm XLPE wires



Outline dimensions

